



SureVoice Panel12

The SureVoice Panel12 is the versatile **controller working position** (CWP) of the SureVoice VCS. The SureVoice Panel12 is a **high-reliable CWP**. It features two 1000 Base-T Gigabit Ethernet jacks with optional PoE to maintain a redundant connection to the network.

Key Features

Connections

- ✓ 2x 1000 Base-T Gigabit Ethernet
- ✓ 2x PoE++
- ✓ 1x Customer specific auxiliary port
- ✓ Optional USB type-C (3.1 gen 1) port

Power

- ✓ Power usage 40 W
- ✓ 15 – 50 VDC input (not needed when PoE is used)

Dimensions

| | |
|---------------|---------|
| Width | 31 cm |
| Height | 21,2 cm |
| Depth | 5,1 cm |

Mounting options

- ✓ VESA 100
- ✓ Free Table Stand, adjustable angle
- ✓ In desk

Interoperability

- ✓ ED-137

Audio

- ✓ 2x Digital connector for External audio
- ✓ Optional external Speaker with handset.

Display

- ✓ 12" Display
- ✓ 1280 x 800
- ✓ Capacitive touch screen
- ✓ Brightness 1000 Cd/m²
- ✓ Viewing angle 85°

Applications

- ✓ VCS system in ATC
- ✓ VCS system in Maritime

Operating environment

| | |
|--------------------|---------------------------|
| Temperature | 0 to 50 °C |
| Humidity | 5 – 95% non-condensing |

Regulations

| | |
|---------------|--------------------|
| EMC | EN 55032, EN 55035 |
| Safety | EN 62368-1 |